

FORMULER

The Digital Innovation Formula!

Z7+

4K 10 bit 60 fps
HDR 10 / High Dynamic Range
HLG / Hybrid Log Gamma

Slim & Compact

Android 7.0



Premium next generation Android OTT middleware and media portal

Cutting-edge features for all your future requirements

The all-new Z7+ has been designed from the ground-up with maximum performance in mind.

Containing the newest decoding technologies and Android 7 Nougat at its core,

the new Z7+ will provide customers with years of streaming media enjoyment through various apps including MYTVOnline.



Air SYNC REMOTE
Fast and easy way to Input Text
Real time Mirror controller

Play Store IPTV Middleware KODI 17+ Quad-Core 3D Games Miracast Micro SD Memory Applications

Android 7.0 VP9 4K 10-bit H.265 HEVC High Efficiency Video Coding Wi-Fi Bluetooth sfallker XTREAM CORES ULTRA LOW POWER USB 3.0 DVB-T2 (T/C) USB

FORMULER

The Digital Innovation Formula!

Z7+



SPECIFICATION

A/V Decoding

Video Decoding	H.265/HEVC Main/Main 10 profile@level 5.1 high-tier, maximum 4K x 2K@60 fps 10-bit decoding H.264/AVC BP/MP/HP@level 5.1, H.264/AVC MVC, maximum 4K x 2K@30 fps decoding Maximum 4K x 2K@60 fps 10-bit VP9 decoding
Video Encoding	H.265 MP@level 5 main tier and H.264 BP/MP/HP@level 4.2 video encoding, maximum 1x1080p@30 fps or 2x720p@30 fps encoding
TV Resolution	720 x 576i, 720 x 480i, 1280 x 720p 1920 x 1080i, 1920 x 1080p, 2160p(4K x 2K)

Audio / Video & Data IN/OUT

HDMI	HDMI 2.0a
USB	1 x USB3.0, 1 x USB2.0
ETHERNET	RJ45 connector, 10/100M
Micro SD Card	Micro SD Card Slot
IR Extension	Removable IR extension
S/PDIF	OPTICAL
Wi-Fi	802.11 b/g/n
BT	V4.0 (optional)

Main System

Main Processor	Hisilicon chipset
Memory	eMMC : 8 GBytes SDRAM : 2 GBytes (DDR4)

Power Supply

Input Voltage	AC 100 ~ 240V, 50/60Hz
Type	Adaptor
Power Consumption	Max. 25W
Standby Power	Max. 0.5W
Protection	Separate Internal Fuse & Lighting protection

Front Panel

Indicators	1 Dual Color LED(Standby, Remote)
------------	-----------------------------------

Physical Specification

Size (W x H x D)	103mm X 18.2mm X 103mm
Operating Temp.	0°C ~ +45°C
Storage Temp.	-10°C ~ +70°C

Accessories



Slim & Compact Design

